

9005H**DIGI-MIG 200LCD PFC****Multiprocess****110V/230V****FEATURES**

- LCD displays 260,000 true colours
- Power factor more than 0.99
- Multiple advantages such as energy saving and wider input voltage
- Works with 110V and 230V
- Capable of loading up to 5kg spool
- Waveform control for added stability of the arc – even at low currents
- Equipped with temperature, voltage and current sensors for high protection
- M15-3 torch and regulator included

**SPECIFICATIONS**

Input power voltage (V)	110/230±10%				
Frequency (Hz)	50/60				
	MIG	TIG	MMA		
Effective current – 110V	23.4	17.7	17.7		
Effective current – 230V	17.7	13.9	20.2		
	MIG	TIG	MMA	MIG	TIG
Rated input current (A)	35	27	27	27	22
Duty cycle (A) (40°C 10 min)	40%@140	40%@100		40%@200	
	60%@115	60%@85		60%@165	
	100%@90	100%@65		100%@130	
No load voltage – limited (V)	67 (MIG) 14 (TIG/MMA)				
Welding current range (A)	25~200 (MIG)				
Welding voltage range (V)	10~27 (MIG)				
Efficiency (%)	80				
Power factor	0.99				
Insulation class	H				
Protection class	IP23				
Cooling	Air				
Overall dimensions (mm)	505 x 210 x 330				
Weight (kg)	15.5				
Accessories included	3m Argon hose + Amphenol plug 3m earth return lead				

